Approval Certificate for Manufacturing Process



[Rolled Steels]

Initial Approval	10th May, 2004		
Manufacturer	Korea Steel Co., Ltd. (Noksan Works)		
	84, Noksansandan 407-ro, Gangseo-gu, Busan, Rep. of Korea		
Product Description	Rolled Steel Sections and Bars for Hull Structure		
	- Grade : A		
	AH32, DH32, EH32		
	AH36, DH36, EH36		
	- See "Appendix 1 "		
Approval Condition	 Raw Materials are to be supplied by the approved manufacturers of this Society or to be satisfactory to the Surveyor. Individual Product Certification is required. 		

THIS IS TO CERTIFY that the manufacturing process for the above mentioned product has been approved in accordance with the relevant requirement of this Society's Rules and/or of the recognized standards as follows.

Pt. 2, Ch. 1, Art. 301 of the Rules for Classification of Steel Ships.

This Certificate is valid until 9th May, 2024

Issued at Gamcheon, Korea on 27th April, 2021



This certificate is signed electronically in accordance with IMO FAL.5/Circ.39/Rev.2. Validation and authentication of the certificate can be confirmed from "http://e-cert.krs.co.kr" by using the tracking No(ME21028755513) and certificate No.(GCH23851-SP001).



KOREAN REGISTER

General Manager of Gamcheon Branch Office

Note: 1. This certificate will be valid subject to complying with the approval conditions described on the certificate and/or on the Rules of this Society.

- 2. This certificate will be invalid from the expiry date aforementioned unless the extension or renewal has been granted to the applicant or the manufacturer.
- 3. Any significant modifications or changes in design or construction to the above product without approval from this Society will render this certificate invalid. 4. Should the specified rules, regulations or standards be amended during the validity of this certificate, the product is to be re-approved by this Society in accordance with the requirements as amended.

Product Description and/or Approval Condition

Date of Issue: 27th April, 2021

◎ Product Description

Z-quality	Grain Refining	Thickness Max. (mm)	Supply Condition (*1)
		15	AR
_	A +V	15	AR (ARS)
Z-quality	Grain Refining	Thickness Max. (mm)	Supply Condition (*1)
-	-	30	AR
_	A I +V	30	AR (ARS)
Z-quality	Grain Refining	Diameter Max. (mm)	Supply Condition (*1)
		65	AR
	- - Z-quality - -	Z-quality Grain Al+V Z-quality Grain Refining Al+V Z-quality Grain	RefiningMax. (mm)15-Al+V15Z-qualityGrain RefiningThickness Max. (mm)30-Al+V30Z-qualityGrain RefiningDiameter Max. (mm)

 AR : As Rolled
 ARS : As Rolled Condition subject to special approval of the Society < End of Page >